

**CHOOSE THE
RIGHT ROGUE.**

	Rogue ES 130I	Rogue ES 180I	Rogue ET 200IP Pro
Rated Output	<p>STICK 25% @ 130 A / 25.2 V (230 V Output) 60% @ 84 A / 23.4 V (230 V Output) 100% @ 65 A / 22.6 V (230 V Output)</p> <p>25% @ 90 A / 23.6 V (120 V Output) 60% @ 58 A / 22.3 V (120 V Output) 100% @ 45 A / 21.8 V (120 V Output)</p> <p>TIG 25% @ 130 A / 15.2 V (230 V Output) 60% @ 84 A / 13.4 V (230 V Output) 100% @ 65 A / 12.6 V (230 V Output)</p> <p>25% @ 130 A / 15.2 V (120 V Output) 60% @ 84 A / 13.4 V (120 V Output) 100% @ 65 A / 12.6 V (120 V Output)</p>	<p>STICK 25% @ 180 A / 27.2 V (230 V Output) 60% @ 116 A / 24.6 V (230 V Output) 100% @ 90 A / 23.6 V (230 V Output)</p> <p>25% @ 110 A / 24.4 V (120 V Output) 60% @ 70 A / 22.8 V (120 V Output) 100% @ 55 A / 22.2 V (120 V Output)</p> <p>TIG 25% @ 180 A / 17.2 V (230 V Output) 60% @ 116 A / 14.6 V (230 V Output) 100% @ 90 A / 13.6 V (230 V Output)</p> <p>25% @ 140 A / 15.6 V (120 V Output) 60% @ 90 A / 13.6 V (120 V Output) 100% @ 70 A / 12.8 V (120 V Output)</p>	<p>STICK 25% @ 200 A / 28.0 V (230 V Output) 60% @ 129 A / 25.2 V (230 V Output) 100% @ 100 A / 24.0 V (230 V Output)</p> <p>25% @ 110 A / 24.4 V (120 V Output) 60% @ 70 A / 22.8 V (120 V Output) 100% @ 55 A / 22.2 V (120 V Output)</p> <p>TIG 25% @ 200 A / 18.0 V (230 V Output) 60% @ 129 A / 15.2 V (230 V Output) 100% @ 100 A / 14.0 V (230 V Output)</p> <p>25% @ 140 A / 15.6 V (120 V Output) 60% @ 90 A / 13.6 V (120 V Output) 100% @ 70 A / 12.8 V (120 V Output)</p>
Max Output	130 A	180 A	200 A
Input Rating	120 V / 230 V VAC +/- 15% (50/60 Hz)	120 V / 230 V VAC +/- 15% (50/60 Hz)	120 V / 230 V VAC +/- 15% (50/60 Hz)
OCV	78 V DC	78 V DC	78 V DC
Max Plate Thickness	1/4"	3/8"	3/8"
Weight	18.2 lb. (8.25 kg)	18.2 lb. (8.25 kg)	21.2 lb. (9.6 kg)
Welding Processes	STICK / LIVE TIG	STICK / LIVE TIG	STICK / HF TIG / LIFT TIG